

ANAEROBIC ACTIVATOR

TECHNICAL DATA SHEET

JULY 2021



PRODUCT DESCRIPTION

Bostik Born2BondTM Anaerobic Activator is a solvent-based product that accelerates and supports anaerobic adhesive curing on passive metals like stainless steel, chromated metals and zinc. It can also accelerate cure speed in larger gaps and increase bonding strength in most cases.

For more information, please consult https://born2bond.bostik.com

KEY FEATURES

- → Can be used at low temperatures (<5°C)
- → On-part lifetime of up to 30 days

DIRECTIONS FOR USE

- Spray Born2Bond[™] Anaerobic Activator on both mating surfaces to be bonded. Treatment of only one surface may be sufficient in the case of small gaps. Use Born2Bond[™] PRE-BONDING CLEANER before application when bonding contaminated surfaces.
- Allow the solvent time to evaporate until the surfaces are completely dry.
- Apply Bostik Born2Bond™ Anaerobic product to one or both surfaces and assemble parts immediately.
- 4. Parts can be handled typically within minutes.

APPLICATIONS

- → For anaerobic adhesives
- → Stainless steel bolts and shafts
- → Threadlocking
- → Pipe sealing
- → Gasketing
- → Retaining

STORAGE/SHELF LIFE

This product is classified as EXTREMELY FLAMMABLE and must be stored in an appropriate manner in compliance with relevant regulations. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not expose to temperatures exceeding 50°C. Keep in properly labelled closed containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Keep/store only in original container.

When stored properly, this material has a shelf life of 24 months.

HEALTH/SAFETY

The Safety Data Sheet is available on the Bostik website and should be consulted for proper handling, cleanup and spill containment before use. Keep containers covered to minimize contamination.

Activator must be handled in a manner applicable to highly flammable materials and in compliance with relevant local regulations. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material.

LIMITATIONS

The solvent can affect certain plastics or coatings. It is recommended to check all surfaces for compatibility before use. This product is not recommended for use in pure oxygen and/or oxygen-rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials. Material removed from containers may be contaminated during use. Do not return product to the original container. Bostik will not assume responsibility for product that has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or customer service representative.



PRODUCT CHARACTERISTICS

Basis Technology	Acetone based
Evaporation	60 seconds
Flammability	Flammable

CONVERSIONS

(°C x 1.8) + 32 = °F	
kV/mm x 25.4 = V/mil	
mm / 25.4 = in	
μm / 25.4 = mil	
N x 0.225 = lb	
N/mm × 5.71 = lb/in	
N/mm² x 145 = psi	
MPa x 145 = psi	
N·m × 8.851 = Ib·in	
N·mm x 0.142 = oz·in	
mPa·s = cP	





PRODUCT DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BOSTIK'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied,

and the equipment used for application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bostik does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS. Nothing contained herein constitutes a license to practice under any patent, and it should not be construed as an inducement to infringe any patent. You are advised to take appropriate steps to be sure that any proposed use of the products will not result in patent infringement.

The information provided herein relates only to the specific products designated and may not be applicable when such products are used in combination with other materials or in any process. The product is sold pursuant to a supply agreement and/or Bostik's Terms and Conditions of Sale, which set forth the sole warranty, if any, that applies to the product. NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR WARRANTY OF MERCHANTABILITY, IS MADE CONCERNING THE PRODUCTS DESCRIBED OR THE INFORMATION PROVIDED HEREIN, AND TO THE MAXIMUM EXTENT ALLOWED BY LAW, SUCH WARRANTIES ARE HEREBY DISCLAIMED. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW.