

STATICIDE ULTRA FLOOR FINISH

Product Code: E46001UF / E46005UF

PRODUCT DESCRIPTION

Staticide Ultra protects tiles from soiling, imparts a high gloss, and controls static generation and dissipation.

PRODUCT USE

Staticide Ultra is specially formulated for controlling static generation on all types of resilient tile, sheet goods, sealed wood and concrete floors, for long periods of time.

FEATURES

- * Non-flammable
- * Provides superior abrasion performance that lasts up to 24 months
- * Is easily maintained and repaired with no buffing, extends stripping/recoating cycle
- * Contains low volatile organic compounds (V.O.C.s)
- * Fast drying, with a high gloss

TOXICITY AND MATERIAL SAFETY

In ready to use form **Staticide Ultra Floor Finish** is safe. In bulk this product is classed as harmful.

TYPICAL PROPERTIES

Density:	1.0
Boiling Point:	100°C
Freezing Point:	Variable
Solubility in Water	Miscible
Odour:	Mild Odour
pH:	7.0 – 9.5
% Volatile:	65
Physical State:	Liquid
Appearance:	Clear or Translucent

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



STATICIDE ULTRA FLOOR FINISH – Page 2

DIRECTIONS FOR USE

1. Strip floors prior to applying **Staticide Ultra**.
2. Rinse twice with clean water in order to remove any residual stripper solution which will not allow the floor finish to cure properly.
3. Seal any unsealed concrete or wood floors.
4. Repair any sealed or epoxy coated concrete floors.
5. Apply three thin coats of **Staticide Ultra**. Use a clean, lint-free rayon string mop that has been rinsed in fresh water then squeezed almost dry. Polish one small section at a time, no longer than 3 metres. DO NOT overlap freshly polished areas.
6. Wait a minimum of 1 hour between each coat. Polish must be completely cured before applying the next coat. Normal traffic may resume in 6-8 hours (preferably overnight) after applying the third coat.
7. Wait 72 hours. Sweep, damp mop with 1 to 1 dilution of **Staticide Ultra** with water, and let floor dry 1 hour before applying coats 4 & 5. Wait at least 3-5 hours between coats. Normal traffic may resume in 6-8 hours (preferably overnight) after applying the final coat.
8. DO NOT perform any additional wet maintenance procedure until the last coat of **Staticide Ultra** has cured for a minimum of 72 hours.

PACKAGING

1 Gallon (US) (3.75 Litres)
5 Gallons (US) (18.75 Litres)

ORDER CODE

E46001UF
E46005UF

ACL Staticide[®]

This product is distributed on behalf of ACL Staticide, 1960 East Devon Avenue, EIK Grove Village, IL 60007 USA. An ISO9002 certified company.

Tel: 847 981 9212 Fax: 847 981 9278 Website: www.aclstaticide.com

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

