

Switch Cleaner Lubricant

Product Code: SWC

PRODUCT DESCRIPTION

A non-flammable solvent / contact lubricant blend designed to remove surface contamination and oxidation from all metallic contact surfaces. Reduces electrical resistance across the switch or connector by increasing the surface area of the contact. Ensures long term protection from corrosion and arcing by depositing a fine film of Electrolube Contact Lubricant.

PRODUCT USE

Primarily for slider / rotary tuners, potentiometers, for friction, ball or roller wiping contacts, slip rings, brushes and commutators. Can also be used in rocker/push-pull switches, edge connectors, plugs and sockets, valve pins, bulb holders, switch gear, locks, hinges and general electro-mechanical uses.

Product doesn't contain any flammable solvents so can safely be sprayed onto live electrical equipment or other sources of ignition without risk.

FEATURES


- * An excellent electrical contact lubricant
- * Reduces contact resistance to a low stable level without altering frequency through the components designed variable setting range
- * Non-silicone, synthetic lubricant, eliminating problems caused by carbon deposits and silicone migration
- * Clear, non-staining, anti-static
- * Conveniently packed in aerosol with extension tube for inaccessible areas
- * Compatible with most plastics, paints and rubbers
- * Prevents capacitance, resistance and frequency deviations, erratic high and low setting spots, sparking and tracking
- * Rapid solvent evaporation ensures swift return to normal operation

**TECHNICAL
DATA
SHEET**



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Switch Cleaner Lubricant – Page 2

Product Code: SWC

TYPICAL PROPERTIES

Liquid density, g/cc:	1.44
Boiling Point, °C (°F)	45 (113)
Vapour Pressure, mm Hg (psia)	347 (6.7)
Flash Point, °C (°F)	
Closed Cup	None
Open Cup	None

PACKAGING

200g Aerosol

ORDER CODE

SWC200D

**TECHNICAL
DATA
SHEET**

Copyright Electrolube 2003

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

